

BEST AVAILABLE COPY

10/20/2005 09:55 2165925009

TUCKER ELLIS

PAGE 03/41

Docket No.: 72255/33238

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl No. : 10/686,233 Confirmation No. : 6359
First Named Applicant : John SANELLI
Filed : October 15, 2003
TC/A.U. : 2821
Examiner : Huedung X. Cao
Customer No. : 23380

US PATENT AND TRADEMARK
OFFICE

REFUND REQUESTED

VIA FACSIMILE ONLY: 703-308-5077

Mail Stop 16
Director of the US Patent
and Trademark Office
PO Box 1450
Alexandria, VA 22313-1450

Dear Sirs:

A refund of the amount of \$100 is requested in connection with the above-identified patent application.

On October 15, 2003, the above-identified patent application was filed with 40 claims total, 2 of which were Independent. Only 38 of the 40 claims were paid for upon filing. March 12, 2004, our Deposit Account was charged \$36.00 for 2 claims in excess of 20. At the time of filing, claims in excess of 20 were \$18.00 each.

On September 14, 2005, an Amendment was filed with 60 claims total, 10 of which are Independent. A credit card form for \$2,400.00 was submitted with the Amendment; \$1,000 to cover Claims in Excess of 20, and \$1,400.00 to cover Independent Claims in excess of 3.

On September 15, 2005, our Deposit Account was charged again for 2 claims in excess of 20 for the above-identified application, this time the current price of \$50.00 per extra claim was charged. Enclosed are the following copies:

1. March 2004 Statement for Deposit Account No. 50-0902.
2. Application as filed.
3. September 2005 Statement for Deposit Account No. 50-0902.
4. Amendment filed on September 14, 2005.

10/20/2005 09:55 2165925009

TUCKER ELLIS

PAGE 04/41

Docket No.: 72255/33238


PATENT
PATENT

2005 OCT 20 11 31 53

Please credit the overpayment of \$100.00 to our Deposit Account No. 50-0902
(72255/33238). If you have any questions please do not hesitate to contact the undersigned. *US PATENT & TRADEMARK OFFICE*

Respectfully Submitted,

Date: 18 October 2005


John X. Garred
Registration No. 31,830
TUCKER ELLIS & WEST LLP
1150 Huntington Building
925 Euclid Avenue
Cleveland, Ohio 44115
Phone: 216-696-3340
Fax 216-592-5009

SEP 14 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl No. : 10/686,233 Confirmation No. 6359
Applicant : John Sanelli
Filed : October 15, 2003
TC/A.U. : 2821
Examiner : Huedung X. Cao
Docket No. : 72255-33238
Customer No. : 23380

FAXED TO: (571) 273-8300

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT

In response to the Office action of June 15, 2005, please amend the above-identified application as follows:

Amendments to the Claims are reflected in the listing of claims which begins on page 2 of this paper.

Amendments to the Drawings begin on page 12 of this paper and include both an attached replacement sheet and an annotated sheet showing changes.

Remarks/Arguments begin on page 13 of this paper.

An Appendix including formal drawing figures is attached following page 15 of this paper.

Adjustment date: 11/30/2005 SDIRETA1
09/15/2005 TL0111 00000008 500902 10686233
02 FC:1202 100.00 CR -1000.00 OP

09/15/2005 TL0111 00000008 500902 10686233

01 FC:1201 1400.00 OP
02 FC:1202 100.00 DA 1000.00 OP

11/30/2005 SDIRETA1 00000008 10686233

01 FC:1202 1000.00 OP

**TUCKER ELLIS & WEST LLP**
ATTORNEYS AT LAW

1150 Huntington Bldg. 925 Euclid Avenue Cleveland, Ohio 44115-1475

phone 216.592.5000 fax 216.592.5009 Web: www.tuckerellis.com

CLEVELAND LOS ANGELES SAN FRANCISCO

FAX
705 307 01 11 31 50
US PATENT & TRADEMARK
OFFICE**ORIGINAL WILL NOT BE SENT**

TO:	COMPANY:	FAX NO:
Mail Stop 16	US Patent and Trademark Office	(703) 308-5077
Commissioner for Patents	(703) 305-4229	

FROM:	<u>John X. Garred</u>	DATE:	<u>10/19/2005</u>	TIME:	<u>4:10:04 PM</u>
Direct Dial:	<u>216.696.3340</u>	E-Mail:	<u>john.garred@tuckerellis.com</u>		
TOTAL NO. OF PAGES:	<u>41</u>	CLIENT/MATTER:	<u>72255/33238</u>		

(including cover page)

COMMENTS**CONFIDENTIALITY NOTICE**

The information in this fax transmission and the documents accompanying it contain confidential information belonging to the sender which is legally privileged. The information is intended only for the use of the individuals or entities named above. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this faxed information is strictly prohibited. If you have received this fax in error, please immediately notify us by telephone to arrange for return of the original documents to us.

PATENT

NAME

2005 OCT 20 10:52:52

PTO/SB/97 (09-04)

Approved for use through 07/31/2006, OMB 0851-0031

U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Certificate of Transmission under 37 CFR 1.8

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office

on 18 OCTOBER 2005
Date

Facsimile No.: 1-703-308-5077
Total Pages: 40


Signature

Mary Erne, Jr.

Typed or printed name of person signing Certificate

Registration Number, if applicable

216-696-4396
Telephone Number

Note: Each paper must have its own certificate of transmission, or this certificate must identify each submitted paper.

- 1) Request for Refund.
- 2) March 2004 Deposit Account Statement.
- 3) Application as filed.
- 4) September 2005 Deposit Account Statement.
- 5) Amendment filed September 14, 2005.

This collection of information is required by 37 CFR 1.8. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1.8 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



United States
Patent and
Trademark Office

USPTO
Home
Page
Finance
Online
Shopping
Page

Deposit Account Statement

Requested Statement Month: March 2004
Deposit Account Number: 500902
Name: TUCKER ELLIS & WEST LLP
Attention: VALERIE SALVINO
Address: 925 EUCLID AVENUE
City: CLEVELAND
State: OH
Zip: 44115
Country: UNITED STATES OF AMERICA

DATE	SEQ	POSTING REF TXT	ATTORNEY DOCKET NBR	FEE CODE	AMT	BAL
03/02	2	10619385	66329/24816	1201	\$518.00	\$3,380.00
03/02	3	10619385	66329/24816	1202	\$180.00	\$3,200.00
03/10	113	09844852	72255/02772	1251	\$110.00	\$3,090.00
03/11	100	E-REPLENISHMENT		9203	-\$640.00	\$3,830.00
* 03/12	28	10688233	72265/33238	1202	\$36.00	\$3,594.00*
03/12	37	10724895	72255/0010	1202	\$54.00	\$3,640.00
03/15	28	E-REPLENISHMENT		9203	-\$50.00	\$3,590.00
START BALANCE			SUM OF CHARGES	SUM OF REPLENISH	END BALANCE	
\$3,896.00			\$896.00	\$590.00	\$3,590.00	

[Need Help?](#) | [USPTO Home Page](#) | [Finance Online Shopping Page](#)

DUAL HEMISPHERE ANTENNA

Background of the Invention

The present invention is directed to the field of wireless networking, with particular applicability to rollouts in which there is a large quantity of wireless traffic in a given operational area. It is becoming increasingly common to implement wireless local area networks (WLANs) in addition to or in place of traditional LANs. In a traditional LAN, each client device, e.g. a personal computer etc., requires a physical, hard-wired connection to the network. However, with a WLAN, each client device includes a wireless capability (such as an insertable, embedded card or fully integrated capability) for wirelessly communicating with the network via an access point (AP) that includes an antenna, a transceiver and a hard-wired connection to the network. In this way, users may carry their hand-held devices and laptop computers within a physical area and still maintain a network connection.

However, in "crowded" enterprise rollouts, it can be difficult for a large number of users to simultaneously access the network due to the contention-based protocol used. Accordingly, it has been contemplated that multiple wireless channels can be used for allowing user access. Three non-overlapping channels have been allocated in the 2.4 GHz band, and eleven channels in the 5 GHz band. Using multiple available channels, an AP may be implemented in a single-package topology that enables simultaneous transmission and reception on nearby frequency channels at the same interval in time. A problem inherent with such a topology is a high degree of self-interference between signals on adjacent channels, resulting in poor quality of service. It is thus desirable to provide signal isolation between each transceiver in the AP. Depending on

the transceiver architecture, there will be an additional antenna-to-antenna isolation requirement that must be met to achieve the overall required signal isolation.

A special problem arises when a multiplicity of antenna elements used to support a single unit, multichannel AP are in close proximity to each other and whose element-to-element isolation is low. The overall requirement is to cover a large (omnidirectional) area with all of the AP channels, either in concert or sectorially. Absorber materials are known for providing antenna isolation, but these materials are expensive, bulky, and otherwise unsuitable as the sole method for achieving the required isolation. Physical separation between the antennas is also a solution, however this would lead to a product that could not be neatly integrated into a single reasonably sized housing. This problem can be also addressed by the use of "smart" antennas, in which the antenna can be "steered" toward a particular client or group of clients to send and receive signals and yet maintain high isolation from other steered beams. Directional antennas with high front-to-back ratios (F/B ratio) can also be used in some applications, such as when a geometrically isolated area must be covered. However, a special case arises when a two channel system is desired. These might be two channels in the 2.4 GHz band or two channels in the 5 GHz band. In these situations, one desires a hemispherical radiation pattern so that the coverage area can be divided into two sectors. The isolation must still be high to allow simultaneous operation of those two transceivers. A novel solution to this special problem is disclosed herein.

Summary of the Invention

The difficulties and drawbacks of previous-type implementations are addressed by the presently-disclosed embodiments in which a wireless device is disclosed, including an antenna system comprising one or more antenna elements for sending and receiving a wireless signal.

One or more conductive members are included, having an edge displaced from and substantially directed toward at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern for a wireless signal.

As will be realized, the invention is capable of other and different embodiments and its several details are capable of modifications in various respects, all without departing from the invention. Accordingly, the drawings and description are to be regarded as illustrative and not restrictive.

Brief Description of the Drawings

Figs. 1A, 1B and 1C respectively show various embodiments of the present antenna system.

Fig. 2 shows the operation of a wireless access point implemented with the present antenna system.

Figs 3A and 3B generally depict antenna gain patterns obtainable with the present antenna system.

Figs. 4A, 4B, 4C, 4D and 4E show various alternate embodiments of a conductive fin as used with the present antenna system.

Figs. 5A, 5B and 5C are diagrams showing various degrees of signal isolation between each antenna in a dual antenna embodiment.

Fig 6 is a diagram showing the antenna gain pattern for a single antenna in a present embodiment.

Detailed Description of the Invention

Particular reference is now made to the figures, where it is understood that like reference numbers refer to like elements. As shown in Fig. 1A, the present antenna system 10 includes one or more antenna elements 12 for sending and receiving a wireless signal. One or more conductive members 14 are provided, preferably in the form of metallic sheets or fins, having an edge 16 displaced from the antenna element 12. The edge 16 is substantially directed toward the antenna element 12. The antenna system 10 is a cooperative component of a radio transceiver including a plurality of radio components for processing a wireless signal, as will be set forth in detail below. It has been observed that a conductive member 14 and an antenna oriented in this manner cooperate in such a way as to establish a hemispherical beam pattern, as will also be set forth in greater detail below.

Applicants have discovered that metallic fins 14 configured with antennas 12 in the disclosed manner simultaneously provide signal isolation and a dual hemispherical radiation pattern for each antenna 12. It has been contemplated that the metallic fins 14 can be formed of brass having a thickness of about 5 mils and dimensions of 3 inches x 4 inches at a nominal operating frequency of 2.4 GHz. Appropriate scaling is required for operation at other frequencies, inversely proportional to frequency. It is of course appreciated that any suitable

metal or other conductor could be substituted for brass. The antennas 12 are preferably dipoles selected to provide a wide bandwidth with a small aperture and a suitable elemental radiation pattern.

In an exemplary embodiment shown in Fig. 1B, two dipole antennas 12 are used with a plurality of metallic fins 14 placed between the antennas, lying in the same plane as the antennas 12. A ground plane 18 may be optionally be included. In this exemplary embodiment, a sandwich module 20 is provided for providing a further level of antenna isolation. The sandwich module 20 includes metal plates 22, preferably formed of brass, which substantially face the metal fins 14, preferably at a perpendicular angle. These plates 22 are preferably electrically separated from the fins 14, though they may optionally be in electrical contact. The sandwich module 20 also preferably includes a separation material 24, which is preferably an RF isolating foam such as AN-77 or another suitable type of material.

Various permutations of element size and orientation were discovered that result in varying degrees of isolation, as will be shown below in the discussion of the other embodiments. For example, as shown in Fig. 1C, the sandwich may alternatively be omitted; an embodiment in which no metal plates 22 or isolating foam is employed. In a further alternate embodiment, brass plates 22 alone may also be employed, without the isolating foam 24. In a further alternate embodiment, brass plates 22 may also be employed, with the isolating foam 24. Table 1 lists various isolation cases of selected permutations of the sandwich module.

Table 1 Isolation vs. Sandwich

Quantity of Conductive Members 14	Composition of Sandwich Module 20	Isolation (dB)
None	Air	22
Two	Air	45
Two	Brass Sheets 22	51
Two	Brass Sheets 22 and AN-77 24	59

Because a dipole is an omni-directional radiating element, the isolation between two antennas is poor without any additional isolation element. For example, at one wavelength of separation (4.8" at 2450 MHz), 2 dipoles have only 22 dB of isolation. However, with the presence of two of the fins 14, an isolation of greater than 45 dB is obtained, as shown in Fig. 5A. However, with the presence of two fins 14 and a separation material 24 (brass sheets), an isolation of greater than 51 dB is obtained, as shown in Fig. 5B. However, with the presence of two fins 14 and a separation material 24 (brass sheets and isolating foam), an isolation greater than 59 dB is obtained, as shown in Fig. 5C. The embodiment of Fig. 1B provides signal isolation between the two dipole antennas of greater than 51 dB in the 2.4 GHz WLAN band, which is a standard band from 2412 to 2484 MHz, as shown in Fig. 5B.

Fig. 6 illustrates the H-Plane radiation pattern of one hemisphere in the embodiment of Fig. 1B. A 3 dB beamwidth is measured in the H-Plane of about 186 degrees, which substantially demonstrates the desired characteristic of a hemispherical coverage antenna element. The resultant pattern demonstrates excellent symmetry and minimal variation over the frequencies of interest. A hemispherical radiation pattern results for each antenna element, thereby providing good radiated power at the points where the channels will overlap, thus minimizing pattern-to-pattern signal minima (or scalloping).

The hemispheric pattern and resulting high isolation obtained by the present arrangement enables a dual hemispherical antenna system in which two antenna elements 12a, 12b of Fig. 2 can be used to cooperate with the conductive member 14. In this way, as especially shown in Fig. 2, each antenna element 12a, 12b can communicate simultaneously on partially-interfering channels within the same wireless band. As shown in the Fig. 2, each antenna element 12a, 12b cooperates with one of a plurality of radio transceivers 30. Each transceiver includes a plurality of respective radio components 32a, 32b for processing a wireless signal. In this manner, one antenna 12a e.g. can transmit while the other antenna 12b receives on a different channel in the same band. As shown in Fig. 3A, each antenna 12a, and 12b would produce its own respective isolated beam pattern 34a, 34b such that a dual hemispheric beam pattern would ideally result with no coupling. However, in practice, as shown in Fig. 3B, the respective beam patterns 34a, 34b are closer to about 186 degrees, and so there is some overlap between the coverage areas of the antenna elements 12a, 12b. Though a minor amount of signal coupling may result in this overlap region, this is nevertheless a satisfactory outcome since it insures a full 360 degree field of coverage for wireless clients.

The benefits of the present system can be realized in a variety of configurations. In one embodiment, for example, a single antenna element 12 can be configured to cooperate with the conductive member 14. In a preferred embodiment, as particularly shown in Figs. 1A, 1B, 1C inter alia, a pair of antenna elements 12 are provided, disposed respectively at opposite ends of the at least one conductive member, and cooperating therewith to establish a respective pair of hemispherical beam patterns.

As is shown in Fig. 4A, a plurality of antenna elements 12a, 12b can be provided, disposed respectively along the periphery the conductive member 14. These antenna elements

12 and the conductive member cooperate therewith to establish a respective plurality of hemispherical beam patterns. A portion of antenna elements 12a, 12b can be adapted to operate over one wireless frequency band, and another portion of antenna elements 12a, 12b can be adapted to operate over a second wireless frequency band. For example, in the four-antenna embodiment shown in Fig. 4A, the antenna elements 12a can be used to operate over the 2.4 GHz band and the other antenna elements 12b can operate over the 5 GHz wireless band. It should be understood that a peripheral arrangement is not limited to four antennas around a square conductive member. Any polygonal arrangement could be contemplated, such as hexagonal or octagonal, without departing from the invention. The isolation in these embodiments will differ from that example provided for the two-element configuration, depending upon the geometrical topology.

Another embodiment of the present antenna system 10 is shown in Fig 4B. A plurality of conductive members 14a, 14b can be provided where each conductive member 14a, 14b is associated with one or more antenna elements 12a, 12b. The conductive members 14a, 14b are preferably discrete fins, oriented at a substantially perpendicular angle, where respective fins 14a are coplanar, and respective other fins 14b are also coplanar. Each conductive member 14a, 14b is preferably associated with a respective pair of antenna elements 12a, 12b, disposed at respective opposite ends of their respective conductive member 14a, 14b. The respective fins 14a, 14b are preferably not connected, intersected members, but these can be made connected and intersecting without departing from the invention. Also, further to the embodiment of Fig. 1B, this embodiment may be configured with a sandwich module, in which the metal plates for one set of antennas 12a form the fins 14b for the respective other set of antennas 14b.

Preferably, the pair of antenna elements 12a associated with a first conductive member 14a is adapted to operate on a first wireless frequency band. The pair of antenna elements 12b associated with a second conductive member 14b is adapted to operate on a second wireless frequency band. The respective wireless frequency bands can be 2.4 GHz and 5 GHz wireless bands. However, it should be understood that this embodiment is not limited to only two bands. The antenna system 10 can include a number of conductive members arranged in a "star" type configuration, with respective pairs of antenna elements, all without departing from the invention.

In the preferred embodiment, the conductive member 14 is two substantially coplanar elements that are coplanar with the one or more antenna elements 12. However, as shown in Fig. 4c, a plurality of planar elements 14 can be provided, substantially coplanar with the antenna element 12. Alternatively, the conductive member 14 can be a substantially contoured member. As shown in Fig. 4D, the substantially contoured conductive member 14 can be an angled member having a vertex edge 40 substantially directed toward the antenna element 12. In general, it has been observed that the isolation and hemispheric beam pattern are obtained by having a sharply defined edge 16 directed toward the antenna element 12. Also, the edge 16 should be parallel with the dipole antenna element 12. In the preferred embodiment, as indicated above, the antenna element 12 is a dipole antenna and the conductive member 14 is one or more discrete components. However, in an alternate embodiment shown in Fig. 4E, one or more antenna elements 12 and conductive members 14 can be formed on a single piece of circuit board material 42, and manufactured thereon by typical processes of circuit board manufacture, e.g. acid etching or machining, etc. In any event, it has been observed that the desirable isolation and

beam pattern were obtained in embodiments where the antenna element 12 is shorter than the respective edge 16 of the conductive member 14.

The present dual hemisphere antenna arrangement provides a 180-degree sector antenna implementation with low "scalping", greater than the gain of an omnidirectional antenna and at least 51 dB of isolation (so as to keep the transmit signal out of the receiver alternate channel). Also, the materials used in the present embodiments are inexpensive and the topology would be straightforward to manufacture. Thus, the present system achieves superior results over previous-type systems with an inexpensive solution that simultaneously has 180° beamwidth and 51 dB of isolation. This is an improvement over known-type sectorized antennas, such as are common in the cellular world, that rely on physical separation, polarization diversity, and expensive diplexers to achieve isolation.

The present conductive member 14 is essentially a reflector screen that provides a high degree of isolation between two dipole antennas, simultaneously yielding a hemispherical radiation pattern in the H-plane. The solution does not require the use of traditional frequency selective surfaces where the benefit might be only 6 dB per octave per surface to get the 51 dB+ isolation. Similarly, the present invention does not require polarization screens since the two antenna elements 12 operate at the same polarization, and a slant polarization would result in a 4 dB penalty of forward gain against the link budget. Finally, the present results are obtained in a compact package which would be very desirable from a consumer marketing standpoint.

As described hereinabove, the present invention solves many problems associated with previous type systems. However, it will be appreciated that various changes in the details, materials and arrangements of parts which have been herein described and illustrated in order to explain the nature of the invention may be made by those skilled in the area within the principle

and scope of the invention will be expressed in the appended claims.

We Claim:

1. An antenna system comprising:

at least one antenna element for sending and receiving a wireless signal;

at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern.

2. The antenna system of claim 1 wherein the at least one antenna element comprises a pair of antenna elements, disposed respectively at opposite ends of the at least one conductive member, and cooperating therewith to establish a respective pair of hemispherical beam patterns.

3. The antenna system of claim 1 wherein the at least one antenna element comprises a plurality of antenna elements, disposed respectively along the periphery of the at least one conductive member, and cooperating therewith to establish a respective plurality of hemispherical beam patterns.

4. The antenna system of claim 3 wherein a first portion of antenna elements are adapted to operate over a first wireless frequency band, and wherein a second portion of antenna elements are adapted to operate over a second wireless frequency band.

5. The antenna system of claim 4 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

6. The antenna system of claim 1 wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.

7. The antenna system of claim 6 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.

8. The antenna system of claim 7 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.

9. The antenna system of claim 8 wherein the pair of antenna elements associated with the first conductive member are adapted to operate in a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate in a second wireless frequency band.

10. The antenna system of claim 9 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.
11. The antenna system of claim 1 wherein the at least one conductive member comprises a single planar element, substantially coplanar with the at least one antenna element.
12. The antenna system of claim 1 wherein the at least one conductive member comprises a plurality of planar elements, substantially coplanar with the at least one antenna element.
13. The antenna system of claim 1 wherein the at least one conductive member comprises a substantially angled member.
14. The antenna system of claim 13 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.

15. The antenna system of claim 1 further comprising a sandwich module for providing a further level of antenna isolation.
16. The antenna system of claim 15 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.
17. The antenna system of claim 15 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.
18. The antenna system of claim 1 wherein the at least one antenna element is a dipole antenna and the at least one conductive member is at least one discrete component.
19. The antenna system of claim 1 wherein the at least one antenna element and at least one conductive member are formed on a single piece of circuit board material.
20. The antenna system of claim 1 wherein the antenna element is shorter than the respective edge of the conductive member.
21. A wireless device comprising:

a radio transceiver comprising a plurality of radio components for processing a wireless signal;

at least one antenna element for sending and receiving a wireless signal;

at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern for the wireless signal.

22. The wireless device of claim 21 wherein the at least one antenna element comprises a pair of antenna elements, disposed respectively at opposite ends of the at least one conductive member, and cooperating therewith to establish a respective pair of hemispherical beam patterns.

23. The wireless device of claim 21 wherein the at least one antenna element comprises a plurality of antenna elements, disposed respectively along the periphery of the at least one conductive member, and cooperating therewith to establish a respective plurality of hemispherical beam patterns.

24. The wireless device of claim 21 wherein a first portion of antenna elements are adapted to operate over a first wireless frequency band, and wherein a second portion of antenna elements are adapted to operate over a second wireless frequency band.

25. The wireless device of claim 24 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

26. The wireless device of claim 21 wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.

27. The wireless device of claim 26 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.

28. The wireless device of claim 27 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.

29. The wireless device of claim 28 wherein the pair antenna elements associated with the first conductive member are adapted to operate on a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate on a second wireless frequency band.

30. The wireless device of claim 29 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

31. The wireless device of claim 21 wherein the at least one conductive member comprises a single planar element, substantially coplanar with the at least one antenna element.

32. The wireless device of claim 21 wherein the at least one conductive member comprises a plurality of planar elements, substantially coplanar with the at least one antenna element.

33. The wireless device of claim 21 wherein the at least one conductive member comprises a substantially angled member.

34. The wireless device of claim 33 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.

33. The wireless device of claim 21 further comprising a sandwich module for providing a further level of antenna isolation.

34. The wireless device of claim 33 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.

35. The wireless device of claim 33 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.

36. The wireless device of claim 21 wherein the at least one antenna element is a dipole antenna and the at least one conductive member is at least one discrete component.

37. The wireless device of claim 21 wherein the at least one antenna element and the at least one conductive member are formed on a single piece of circuit board material.

38. The wireless device of claim 21 wherein the antenna element is shorter than the respective edge of the conductive member.

ABSTRACT OF THE DISCLOSURE

A wireless device is disclosed, including an antenna system comprising one or more antenna elements for sending and receiving a wireless signal. One or more conductive members are included, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a multiplicity of hemispherical beam patterns for a wireless signal. Embodiments with a multiplicity of antenna elements exhibit a high degree of isolation between said antenna elements.



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

MONTHLY STATEMENT
OF DEPOSIT ACCOUNT

To replenish your deposit account, detach and return top portion with your check. Make check payable to Director of Patents & Trademarks.

TUCKER ELLIS & WEST LLP
VALERIE SALVINO
925 EUCLID AVENUE
SUITE 1100
CLEVELAND OH 44115

FINA

Account No.	500902
Date	9-30-05
Page	1

PLEASE SEND REMITTANCES TO:
U. S. Patent and Trademark Office
P.O. Box 70541
Chicago, IL 60673

DATE POSTED			CONTROL NO.	DESCRIPTION (Serial, Patent, TM, Order)	DOCKET NO.	FEE CODE	CHARGES/ CREDITS	BALANCE
MO.	DAY	YR.						
9	15	05	11	10686233	72255/33238	1202	100.00	5280.00
<div>AN AMOUNT SUFFICIENT TO COVER ALL SERVICES REQUESTED MUST ALWAYS BE ON DEPOSIT</div> <div> <div>OPENING BALANCE</div> <div>5820.00</div> </div> <div> <div>TOTAL CHARGES</div> <div>750.00</div> </div> <div> <div>TOTAL CREDITS</div> <div>5074.00</div> </div> <div> <div>CLOSING BALANCE</div> <div>10144.00</div> </div>								

MS0205 (8/2004)

*** O.D. INDICATES OVERDRAWN

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl No. : 10/686,233 Confirmation No. 6359
Applicant : John Sanelli
Filed : October 15, 2003
TC/A.U. : 2821
Examiner : Huedung X. Cao
Docket No. : 72255-33238
Customer No. : 23380

FAXED TO: (571) 273-8300

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

AMENDMENT

In response to the Office action of June 15, 2005, please amend the above-identified application as follows:

Amendments to the Claims are reflected in the listing of claims which begins on page 2 of this paper.

Amendments to the Drawings begin on page 12 of this paper and include both an attached replacement sheet and an annotated sheet showing changes.

Remarks/Arguments begin on page 13 of this paper.

An Appendix including formal drawing figures is attached following page 15 of this paper.

Appl No. 10/686,233
Amndt dated September 15, 2005
Reply to Office action of June 15, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended): An antenna system comprising:
at least one plurality of active antenna elements for sending and receiving a wireless signal;
at least one passive conductive member, having [[an]] edges displaced from and substantially directed toward the at least one plurality of active antenna elements, and cooperating therewith to establish a plurality of hemispherical beam patterns.
2. (Canceled):
3. (Currently Amended): The antenna system of claim 1 wherein the at least one plurality of active antenna elements ~~comprises a plurality of antenna elements, are~~ disposed respectively along the periphery of the at least one conductive member, and cooperating therewith to establish a respective plurality of hemispherical beam patterns.
4. (Original): The antenna system of claim 3 wherein a first portion of antenna elements are adapted to operate over a first wireless frequency band, and wherein a second portion of antenna elements are adapted to operate over a second wireless frequency band.
5. (Original): The antenna system of claim 4 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.
6. (Original): The antenna system of claim 1 wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.

Appl No. 10/686,233
Amdt. dated September 15, 2005
Reply to Office action of June 15, 2005

7. (Original): The antenna system of claim 6 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.
8. (Original): The antenna system of claim 7 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.
9. (Original): The antenna system of claim 8 wherein the pair of antenna elements associated with the first conductive member are adapted to operate in a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate in a second wireless frequency band.
10. (Original): The antenna system of claim 9 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.
11. (Original): The antenna system of claim 1 wherein the at least one conductive member comprises a single planar element, substantially coplanar with the at least one antenna element.
12. (Original): The antenna system of claim 1 wherein the at least one conductive member comprises a plurality of planar elements, substantially coplanar with the at least one antenna element.
13. (Original): The antenna system of claim 1 wherein the at least one conductive member comprises a substantially angled member.
14. (Original): The antenna system of claim 13 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.

Appl No. 10/686,233
Amdt. dated September 15, 2005
Reply to Office action of June 15, 2005

15. (Original): The antenna system of claim 1 further comprising a sandwich module for providing a further level of antenna isolation.
16. (Original): The antenna system of claim 15 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.
17. (Original): The antenna system of claim 15 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.
18. (Original): The antenna system of claim 1 wherein the at least one antenna element is a dipole antenna and the at least one conductive member is at least one discrete component.
19. (Original): The antenna system of claim 1 wherein the at least one antenna element and at least one conductive member are formed on a single piece of circuit board material.
20. (Original): The antenna system of claim 1 wherein the antenna element is shorter than the respective edge of the conductive member.
21. (Currently Amended): A wireless device comprising:
a radio transceiver comprising a plurality of radio components for processing a wireless signal;
at least one plurality of active antenna elements for sending and receiving a wireless signal;
at least one passive conductive member, having [[an]] edges displaced from and substantially directed toward the at least one plurality of active antenna elements, and cooperating therewith to establish a plurality of hemispherical beam patterns for the wireless signal.

Claim 22 (canceled)

Appl No. 10/686,233
Amtd. dated September 15, 2005
Reply to Office action of June 15, 2005

23. (Currently Amended): The wireless device of claim 21 wherein ~~the at least one plurality of active antenna elements comprises a plurality of antenna elements, are~~ disposed respectively along the periphery of the at least one conductive member, and cooperating therewith to establish a respective plurality of hemispherical beam patterns.

24. (Original): The wireless device of claim 21 wherein a first portion of antenna elements are adapted to operate over a first wireless frequency band, and wherein a second portion of antenna elements are adapted to operate over a second wireless frequency band.

25. (Original): The wireless device of claim 24 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

26. (Original): The wireless device of claim 21 wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.

27. (Original): The wireless device of claim 26 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.

28. (Original): The wireless device of claim 27 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.

29. (Original): The wireless device of claim 28 wherein the pair antenna elements associated with the first conductive member are adapted to operate on a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate on a second wireless frequency band.

30. (Original): The wireless device of claim 29 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

Appl No. 10/686,233
Amtd. dated September 15, 2005
Reply to Office action of June 15, 2005

31. (Original): The wireless device of claim 21 wherein the at least one conductive member comprises a single planar element, substantially coplanar with the at least one antenna element.

32. (Original): The wireless device of claim 21 wherein the at least one conductive member comprises a plurality of planar elements, substantially coplanar with the at least one antenna element.

33. (Original): The wireless device of claim 21 wherein the at least one conductive member comprises a substantially angled member.

34. (Original): The wireless device of claim 33 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.

35. (Currently Amended): The wireless device of claim 21 further comprising a sandwich module for providing a further level of antenna isolation.

36. (Currently Amended): The wireless device of claim 33 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.

37. (Currently Amended): The wireless device of claim 33 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.

38. (Currently Amended): The wireless device of claim 21 wherein the at least one antenna element is a dipole antenna and the at least one conductive member is at least one discrete component.

App'l No. 10/686,233
Amtd. dated September 15, 2005
Reply to Office action of June 13, 2005

3739. (Currently Amended): The wireless device of claim 21 wherein the at least one antenna element and the at least one conductive member are formed on a single piece of circuit board material.

3840. (Currently Amended): The wireless device of claim 21 wherein the antenna element is shorter than the respective edge of the conductive member.

41. (New) An antenna system comprising:
- at least one antenna element for sending and receiving a wireless signal; and
 - at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern;
- wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.
42. (New): The antenna system of claim 41 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.
43. (New): The antenna system of claim 42 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.
44. (New): The antenna system of claim 43 wherein the pair of antenna elements associated with the first conductive member are adapted to operate in a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate in a second wireless frequency band.
45. (New): The antenna system of claim 44 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

App No. 10/686,233
Amtd. dated September 15, 2005
Reply to Office action of June 15, 2005

46. (New): An antenna system comprising:
- at least one antenna element for sending and receiving a wireless signal; and
 - at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern;
- wherein the at least one conductive member comprises a substantially angled member.
47. (New): The antenna system of claim 46 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.
48. (New): An antenna system comprising:
- at least one antenna element for sending and receiving a wireless signal;
 - at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern; and
- a sandwich module for providing a further level of antenna isolation.
49. (New): The antenna system of claim 48 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.
50. (New): The antenna system of claim 49 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.
51. (New): An antenna system comprising:
- at least one antenna element for sending and receiving a wireless signal; and
 - at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern;

Appl No. 10/636,233
Amdt. dated September 15, 2005
Reply to Office action of June 15, 2005

wherein the antenna element is shorter than the respective edge of the conductive member.

52. (New): A wireless device comprising:

a radio transceiver comprising a plurality of radio components for processing a wireless signal;

at least one antenna element for sending and receiving a wireless signal; and

at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern for the wireless signal;

wherein the at least one conductive member comprises a plurality of non-intersecting conductive members wherein each conductive member is associated with at least one antenna element.

53. (New): The wireless device of claim 52 wherein the plurality of conductive members comprise first and second conductive members, located at a substantially perpendicular angle.

54. (New): The wireless device of claim 53 wherein each conductive member is associated with a pair of antenna elements, disposed at respective opposite ends of the respective conductive member.

55. (New): The wireless device of claim 54 wherein the pair antenna elements associated with the first conductive member are adapted to operate on a first wireless frequency band and the pair of antenna elements associated with the second conductive member are adapted to operate on a second wireless frequency band.

56. (New): The wireless device of claim 55 wherein the first and second wireless frequency bands are 2.4 GHz and 5 GHz wireless bands.

57. (New): A wireless device comprising:

Appl No. 10/686,233
Amtd. dated September 13, 2005
Reply to Office action of June 13, 2005

a radio transceiver comprising a plurality of radio components for processing a wireless signal;
at least one antenna element for sending and receiving a wireless signal; and
at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern for the wireless signal;
wherein the at least one conductive member comprises a substantially angled member.

58. (New): The wireless device of claim 57 wherein the substantially contoured member is an angled member having a vertex edge substantially directed toward the at least one antenna element.

59. (New): A wireless device comprising:
a radio transceiver comprising a plurality of radio components for processing a wireless signal;
at least one antenna element for sending and receiving a wireless signal;
at least one conductive member, having an edge displaced from and substantially directed toward the at least one antenna element, and cooperating therewith to establish a hemispherical beam pattern for the wireless signal; and
a sandwich module for providing a further level of antenna isolation.

60. (New): The wireless device of claim 59 wherein the sandwich module comprises metal plates that substantially face the at least one conductive member at a perpendicular angle.

61. (New): The wireless device of claim 59 where the sandwich module comprises a separation material having RF isolating properties, for providing a further level of antenna isolation.

62. (New): A wireless device comprising:
a radio transceiver comprising a plurality of radio components for processing a wireless signal;

Appl No. 10/686,233
Amdt. dated September 15, 2005
Reply to Office action of June 15, 2005

at least one antenna element for sending and receiving a wireless signal; and
at least one conductive member, having an edge displaced from and substantially directed
toward the at least one antenna element, and cooperating therewith to establish a hemispherical
beam pattern for the wireless signal;

wherein the antenna element is shorter than the respective edge of the conductive
member.

Appl No. 10/686,233
Amtd. dated September 15, 2005
Reply to Office action of June 15, 2005

Amendments to the Drawings:

Submitted herewith are formal drawings. There is no new matter in the drawings.

Attachment: Replacement Sheets

Appl No. 10/686,233
Amdt dated September 15, 2005
Reply to Office action of June 15, 2005

REMARKS/ARGUMENTS

The applicant would like to acknowledge, with thanks, the Office Action mailed June 15, 2005. This amendment and response is responsive to the Office Action mailed June 15, 2005.

The examiner objected to misnumbered claims 33-34. The examiner renumbered claims 33 and 34 to 35 and 36 and renumbered claims 35-38 to 37-40 respectively. Accordingly, claims 35-40 are amended herein to correspond with the examiner's renumbering.

New claims 41 is claim 6 rewritten in independent form. The examiner indicated claim 6 would be allowable if rewritten in independent form containing all of the limitations of the base claim and any intervening claims. New claims 42-45 are the equivalent of claims 7-10 and directly depend from new claim new 41 (the equivalent of claim 6 containing all of the limitations of the base claim and any intervening claims) and should thus be allowable.

Claim 46 is the equivalent of claim 13 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated would be allowable. Claim 47 is the equivalent of claim 14 depending from claim 46 (which is the equivalent of claim 13 containing all of the limitations of the base claim and any intervening claims), and thus should be in condition for allowance.

New claim 48 is the equivalent of claim 15 rewritten in independent form a containing all of the limitations of the base claim and any intervening claims, which the examiner indicated would be allowable. New claims 49-50 are the equivalent of claims 16-17 dependent on claim 48 (the equivalent of claim 15 containing all of the limitations of the base claim and any intervening claims).

New claim 51 is the equivalent of claim 20 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated would be allowable.

New claim 52 is the equivalent of claim 26 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated would be allowable. Claims 53-56 are the equivalent of claims 26-30 depending from claim 52 (the equivalent of claim 26 containing all of the limitations of the base claim and any intervening claims) which the examiner indicated would be allowable.

New claim 57 is the equivalent of claim 33 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated

Appl No. 10/686,233
Amended September 15, 2005
Reply to Office action of June 15, 2004

would be allowable. Claim 58 is the equivalent of claims 34 which is dependent on claim 57 (the equivalent of claim 33 containing all of the limitations of the base claim and any intervening claims), and thus should be in condition for allowance.

Claim 59 is the equivalent of claim 35 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated as allowable. Claims 60-61 are the equivalent of claims 36-37 dependent on claim 59 (the equivalent of claim 35 containing all of the limitations of the base claim and any intervening claims) and thus should be in condition for allowance. Claim 62 is the equivalent of claim 40 rewritten in independent form containing all of the limitations of the base claim and any intervening claims, which the examiner indicated as allowable.

I. Rejections under 35 U.S.C. § 102 and 35 U.S.C. § 103

Claims 1-4, 11-12 and 18-19, 21-24, 31-32 and 38-39 stand rejected as anticipated by U.S. Patent No. 6,864,852 B2 to Chiang et al. (hereinafter Chiang). Claims 5 and 25 stand rejected as being obvious in view of Chiang. Claims 2 and 22 have been cancelled. For reasons that will now be set forth, claims 1, 3-5, 11-12, 18-19, 21, 23-24, 31-32 and 38-39 as currently amended are not anticipated or obvious based on Chiang.

Independent claims 1 and 21 as currently amended recite an apparatus (an antenna system and wireless device respectively) comprising a plurality of active antenna elements for sending and receiving a wireless signal and at least one passive conductive member, having edges displaced from and substantially directed toward the plurality of active antenna elements, and cooperating therewith to establish a plurality of hemispherical beam patterns. By contrast, Chiang discloses antenna arrays that has a single active element (reference number 202) and passive elements (reference number 200 in Fig. 4 or passive dipoles 308 in Fig. 20) that shape the radiation pattern from (or to) the active element (see col. 7, lines 34-36; col. 15, lines 59-61. The active element is in the center of the antenna system and the passive elements (e.g., *passive dipoles*) surround the active element. Thus, Chiang does not disclose, teach, suggest or motivate, a system comprising a plurality of active antenna elements for sending and receiving a wireless signal and at least one passive conductive member, having edges displaced from and substantially directed toward the plurality of active antenna elements, and cooperating therewith to establish a plurality of hemispherical beam patterns.

Appl No. 10/686,233
Amdt. dated September 15, 2005
Reply to Office action of June 15, 2005

Claims 3-20 and 23-40 are directly dependent from claims 1 and 21 respectively and therefore contain each and every element of claims 1 and 21 respectively. Therefore, for the reasons already set forth for claims 1 and 21, claims 3-20 and 23-40 are not anticipated or obvious in view of Chiang.


In addition to the reasons set forth above, claims 3 and 23 recite that the plurality of antenna elements are disposed along the periphery of the at least one conductive member. By contrast, the systems disclosed by Chiang have passive elements disposed along the periphery of the (single) active element (see Figs 3-5, 7, 9, 11, 13, 15, 17 and 19-20. Thus, in addition to the reasons set forth above, Chiang does not disclose, teach, suggest or motivate the subject matter of claims 3 and 23.

II. Conclusion

A credit card payment for the additional claim fees is being submitted with this amendment. If there are any fees necessitated by the foregoing communication, please charge such fees to our Deposit Account No. 50-0902, referencing our Docket No. 72255-33238.

Respectfully submitted,
TUCKER, ELLIS & WEST

Date: 9-14-2005


Larry B. Donovan
Registration No. 47,230
1150 Huntington Building
925 Euclid Avenue
Cleveland, Ohio 44115-1475
Customer No. 23380
(216) 696-3864 (phone)
(216) 592-5009 (fax)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.